



ETA-Danmark A/S
Göteborg Plads 1
DK-2150 Nordhavn
Tel. +45 72 24 59 00
Fax +45 72 24 59 04
Internet www.etadanmark.dk

Authorised and notified according
to Article 29 of the Regulation (EU)
No 305/2011 of the European
Parliament and of the Council of 9
March 2011

MEMBER OF EOTA



European Technical Assessment ETA-17/0206 of 03/04/2017

I General Part

Technical Assessment Body issuing the ETA and designated according to Article 29 of the Regulation (EU) No 305/2011: ETA-Danmark A/S

Trade name of the construction product:

Wütop Thermo ND Plus

Product family to which the above construction product belongs:

Membrane for use as roof underlay

Manufacturer:

Adolf Würth GmbH & Co. KG
Reinhold Würth Strasse 12 – 17
D-74650 Künzelsau
Internet www.wuerth.com

Manufacturing plant:

Adolf Würth GmbH & Co. KG
Reinhold Würth Strasse 12 – 17
D-74650 Künzelsau

This European Technical Assessment contains:

6 pages

This European Technical Assessment is issued in accordance with Regulation (EU) No 305/2011, on the basis of:

EAD 030218-00-0402 - Membrane for use as roof underlay – edition December 2016

This version replaces:

Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and should be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full (excepted the confidential Annex(es) referred to above). However, partial reproduction may be made, with the written consent of the issuing Technical Assessment Body. Any partial reproduction has to be identified as such.

II SPECIFIC PART OF THE EUROPEAN TECHNICAL ASSESSMENT

1 Technical description of product and intended use

Technical description of the product

General

The membranes consist of multilayer flexible sheets. They are diffusion open membranes with increased UV resistance, perforation resistance, resistance to water pressure and tightness of perforations from nails and screws.

The membranes consist of a polyester and a polyurethane (TPU) coating.

Designation	Wütop Thermo ND Plus
Characteristics	
Composition	Unwoven polyester / polyurethane (TPU) coating
Total weight	230 g/m ²
Minimum slope	≥ 14°
Assembly method in overlaps	Gluing

The roof underlay membranes are fastened to the timber joists with nails or screws. No additional nail sealing material is necessary on a full-surface pressure-resistant substrate. In the case of non-full-surface, the nail and screw holes are waterproofed with nail sealing tape Eurasol® PE.

The roofing membrane is installed with specified Würth accessories. Connection details are made with the Eurasol Thermo HT adhesive tape and the adhesive Wütop WRD.

2 Specification of the intended use in accordance with the applicable EAD

The membranes are intended for use as underlays, which are to be used under roof covering of roofs with roof pitch from 14° to 90°.

The membranes are intended to be used in high altitude and to be exposed to weathering (UV, rain) for a defined extended period of time up to 3 months.

The provisions made in this European Technical Assessment are based on an assumed intended working life of the roof underlay of 10 years.

The indications given on the working life cannot be interpreted as a guarantee given by the producer or Assessment Body, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

Characteristic

Assessment of characteristic

3.2 Safety in case of fire (BWR2)

Reaction to fire

The membranes obtain the following classification in accordance with EN 13501-1 and Delegated Regulation 2016/364

Designation	Wütop Thermo ND Plus
Class	E
End use condition	With any A1 or A2-s1,d0 class substrate with a density $\geq 652 \text{ kg/m}^3$.

3.3 Hygiene, health and the environment (BWR3)

Resistance to water penetration

W1 according to 13859-1

Water vapour transmission

Sd = 0,13 m

Tensile properties

Designation	Wütop Thermo ND Plus
Characteristics	
Tensile properties	
Longitudinal, initial	Mean value: $F_{\max} = 310 \text{ N/50mm}$ Elongation: 50%
Longitudinal, aged	Mean value: $F_{\max} = 310 \text{ N/50mm}$ Elongation: 50%
Transverse, initial	Mean value: $F_{\max} = 360 \text{ N/50mm}$ Elongation: 50%
Transverse, aged	Mean value: $F_{\max} = 360 \text{ N/50mm}$ Elongation: 50%

Resistance to tearing

Designation	Wütop Thermo ND Plus
Characteristics	
Resistance to tearing	
Longitudinal, initial	Mean value: $F_{\max} = 210 \text{ N}$
Longitudinal, aged	NPA
Transverse, initial	Mean value: $F_{\max} = 210 \text{ N}$
Transverse, aged	NPA

Resistance to perforation

No Performance assessed

Dimensional stability	- 2 % both longitudinal and transverse
Flexibility at low temperature	T_B ≤ -20 °C
Resistance to artificial ageing:	
UV resistance 5000h	No Performance assessed. Requirement fulfilled after 336 h UV exposure
Exposure to heat	See above
Resistance to penetration of air	0,0028 m³/(m² × h × 50 Pa)
	Wütop Thermo ND Plus with including Adhesive sealing tape (2SK) or Adhesive sealing tape Eurasol® Thermo HT
Water tightness of seams	The seams with 50 mm width are watertight at a water pressure of 600 Pa (60 mm water column)
Emissivity	No Performance Assessed
	1. Wütop Thermo ND Plus. No additional nail sealing material is necessary on a full-surface pressure-resistant substrate
Tightness of perforations from nails and screws	2. Wütop Thermo ND Plus with nail sealing tape Eurasol PE, in the case of non-full-surface.
	The perforations are water tight when subjected to heavy rain of 2 l / m² × min up to a wind pressure of 600 Pa.

Aspects related to the performance of the product

The European Technical Assessment is issued for the product on the basis of agreed data/information, deposited with ETA-Danmark, which identifies the product that has been assessed and judged. Changes to the product or production process, which could result in this deposited data/information being incorrect, should be notified to ETA-Danmark before the changes are introduced. ETA-Danmark will decide whether or not such changes affect the ETA and consequently the validity of the CE marking on the basis of the ETA and if so whether further assessment or alterations to the ETA, shall be necessary.

The performance of the membranes results from the characteristic values and categories.

The supplementing statements of the manufacturer stated in the MTD for design and application of the membrane for creating a roof underlay with the appropriate performance shall be considered

The performance of the membranes in use as roof underlay can be assumed only, if the following aspects are considered:

- only those ancillary components which are specified by the ETA can be used,
- the appropriate tools shall be used and adjuvant, precautions shall be taken,
- inspecting the substrate surface for appropriateness and correct treatment,
- inspection in the process of establishing the roof underlay and of the finished installation and documentation of the results.

The information as to the handling of waste products shall be observed.

It is the manufacturer's responsibility to make sure that all those who utilize the membrane will be appropriately informed about the specific conditions according to this ETA and the not confidential parts of the MTD deposited to this ETA.

4 Attestation and verification of constancy of performance (AVCP)

4.1 AVCP system

According to the decision Decision 99/90/EC and 2001/596/EC of the European Commission as amended, the system(s) of assessment and verification of constancy of performance (see Annex V to Regulation (EU) No 305/2011) is 3.

5 Technical details necessary for the implementation of the AVCP system, as foreseen in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at ETA-Danmark prior to CE marking.

Issued in Copenhagen on 2017-04-03 by



Thomas Bruun
Managing Director, ETA-Danmark