

Rinforzo laterale Standard Universal



CERTIFICAZIONI



Korea Fire Institute

CARATTERISTICHE

Utilizzabile per rinforzi laterali e longitudinali

La testa del bullone a serraggio controllato permette una rapida installazione e ispezione dei rinforzi antisismici

Works with 1" through 2" brace pipes to reduce inventory

Il design asolato aggancia la tubazione per una maggior forza di presa

Soddisfa i requisiti NFPA®-13 per i rinforzi antisismici

Meets CEN/TS 17551:2021 requirements for Seismic Sway Bracing

SPECIFICATIONS

Materiale: Steel;Cast Iron

Finitura: Elettrozincato

Table 1/1

Numero catalogo	Codice articolo	NB/DN (Diametro nominale)	A	B	Certificazioni
-----------------	-----------------	---------------------------	---	---	----------------

CSBSTU0100EG	404385	25	174.6 mm	25 mm	UL, AON Fire Protection, Rigid Seismic, OSHPD, cUL, FM Approved, Seismic
CSBSTU0125EG	404386	32	187.4 mm	25.4 mm	cUL, FM Approved, Seismic, UL, AON Fire Protection, Rigid Seismic, OSHPD
CSBSTU0150EG	404387	40	196.9 mm	25.4 mm	UL, AON Fire Protection, Rigid Seismic, OSHPD, cUL, FM Approved, Seismic
CSBSTU0200EG	404388	50	206.4 mm	30.2 mm	OSHPD, cUL, FM Approved, Seismic, UL, AON Fire Protection, Rigid Seismic
CSBSTU0250EG	404389	65	225.4 mm	30.2 mm	UL, AON Fire Protection, Rigid Seismic, OSHPD, cUL, FM Approved, Seismic
CSBSTU0300EG	404390	80	238.1 mm	30.2 mm	UL, AON Fire Protection, Rigid Seismic, OSHPD, cUL, FM Approved, Seismic
CSBSTU0400EG	404391	100	269.9 mm	38.1 mm	cUL, FM Approved, Seismic, UL, AON Fire Protection, Rigid Seismic, OSHPD
CSBSTU0500EG	404392	125	308 mm	38.1 mm	UL, AON Fire Protection, Rigid Seismic, OSHPD, cUL, FM Approved, Seismic
CSBSTU0600EG	404393	150	346.1 mm	50.8 mm	cUL, FM Approved, Seismic, UL, AON Fire Protection, Rigid Seismic, OSHPD

CSBSTU0800EG	404394	200	400.1 mm	50.8 mm	Korea Fire Institute, Rigid Seismic, ENG, UL, AON Fire Protection, Rigid Seismic, OSHPD, cUL, FM Approved, Seismic
CSBSTU1000EG	404395	250	457.2 mm	50.8 mm	UL, AON Fire Protection, Rigid Seismic, Korea Fire Institute, Rigid Seismic, KOR, OSHPD, cUL, FM Approved, Seismic

ADDITIONAL PRODUCT DETAILS

When installed with Schedule 10 and Schedule 40 Service Pipe, use 1" to 2" Schedule 40 NPS as brace member.

When installed with KS D 3507 and KS D 3562 Service Pipe, use 25A to 32A KS D 3562 as brace member.



Carichi UL				
Pezzo numero	Laterale		Longitudinale	
	Tubazione schedula 10/schedula 40	Tubazione KS D 3507/ KS D 3562	Tubazione schedula 10/schedula 40	Tubazione KS D 3507/ KS D 3562
CSBSTU0200	5338 N	N/D	3114 N	N/D
CSBSTU0250	8896 N	N/D	5782 N	N/D
CSBSTU0300	7117 N	N/D	3114 N	N/D
CSBSTU0400	8896 N	N/D	5782 N	N/D
CSBSTU0500	8896 N	N/D	5782 N	N/D
CSBSTU0600	4893 N	N/D	4893 N	N/D
CSBSTU0800	8896 N	8896 N	6094 N	6094 N
CSBSTU1000	8895 N	8895 N	8385 N	8385 N

Carichi secondo FM (Tubi di servizio EN 10255 L, EN10255 M e EN 10255 H)								
Pezzo numero	Capacità orizzontale per angolo di installazione da verticale							
	Laterale				Longitudinale			
	30°- 44°	45°- 59°	60°- 74°	75°- 90°	30°- 44°	45°- 59°	60°- 74°	75°- 90°
CSBSTU0100xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0125xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0150xx	3825 N	5425 N	6670 N	7430 N	4315 N	3200 N	3825 N	4270 N
CSBSTU0200xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0250xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0300xx	6805 N	9610 N	11790 N	13165 N	3870 N	3070 N	3690 N	4136 N
CSBSTU0400xx	6985 N	9875 N	12100 N	13480 N	6895 N	6185 N	7475 N	8320 N
CSBSTU0500xx	6985 N	9875 N	12100 N	13480 N	6895 N	6185 N	7475 N	8320 N
CSBSTU0600xx	8805 N	12500 N	15300 N	17080 N	6540 N	5205 N	6270 N	6985 N

Carichi secondo FM (muro da 4,8 mm e tubi di servizio EN 10255 H)								
Pezzo numero	Capacità orizzontale per angolo di installazione da verticale							
	Laterale				Longitudinale			
	30°- 44°	45°- 59°	60°- 74°	75°- 90°	30°- 44°	45°- 59°	60°- 74°	75°- 90°
CSBSTU0800xx	9075 N	12855 N	15745 N	17570 N	5340 N	7560 N	9295 N	10365 N
CSBSTU1000xx	9075 N	12855 N	15745 N	17570 N	5340 N	7560 N	9295 N	10365 N

Carichi UL (elencati per restrizioni)		
Pezzo numero	Tubazione schedula 10	Tubazione schedula 40
CSBSTU0100	2914 N	2914 N
CSBSTU0125	2914 N	2914 N
CSBSTU0150	2914 N	2914 N
CSBSTU0200	2914 N	N

SCHEMI



AVVERTENZA

AVVERTENZA: i prodotti nVent devono essere installati e usati solo secondo le indicazioni riportate nei fogli delle istruzioni del prodotto nVent e nei materiali di formazione. I fogli di istruzioni sono disponibili sul sito www.nvent.com e presso il vostro rappresentante locale dell'assistenza clienti di nVent. Un'installazione scorretta, l'uso improprio, l'applicazione errata

o altre inosservanze delle istruzioni e delle avvertenze di nVent possono causare un malfunzionamento del prodotto, danni alle proprietà, lesioni corporee gravi e morte e/o l'annullamento della garanzia.

America del Nord

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europa

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

